



### PRODUCT DESCRIPTION

Dimensions	2038mm x 190mm
Thickness	9mm
Bevels	4
Loc System	5G Loc under licence of Välinge Innovation AB
Classification of use	Class 23/32 According to European Standard EN13329

	Contains	m <sup>2</sup>	ft <sup>2</sup>	Weight
1 pack	5 planks	1,94 m <sup>2</sup>	20,84 ft <sup>2</sup>	15,9 kg
1 pallet	72 packs	139,4 m <sup>2</sup>	1500,48 ft <sup>2</sup>	1173 kg

### COMPOSITION

Surface layer	Direct laminated paper, impregnated with melamine resin
Substrate	Moisture resistant High Density Fiberboard (HDF)
Backing	Direct laminated paper, impregnated with melamine resin

### TESTED VALUE

Abrasion resistance

### METHOD

EN13329

### TEST RESULTS

AC4 (IP≥4000)

Impact resistance

EN13329

Small ball : ≥ 12 N - Big ball : ≥ 750 mm

Thickness swelling

EN13329

12% (requirement ≤ 18%)

Fire resistance

EN14041

Cfl-S1

Formaldehyde

EN14041

E1

Slipperiness

EN14041

DS

Density

EN323

900 kg

Resistance to staining

EN438

5 (groups 1+2); 4 (group 3)

Resistance to cigarette burns

EN438

4

Effect of a furniture leg

EN424

No damage (foot type 0)

Effect of a castor chair

EN425

No change in appearance or damage

Thermal resistance in combination with underlay Excellence Plus

0,09 m<sup>2</sup>K/W – Suitable for floor heating/cooling. Detailed instructions on [www.berryalloc.com](http://www.berryalloc.com)

### CERTIFICATES/LABELS

- Sustainability of forests: PEFC certified (07-31-229)
- Labelling according to French VOC emission regulation: A+
- CARB: Phase II compliant
- DOP : 170-DL3213-1

### WARRANTY

- Lifetime Residential Warranty
- 5 Years of Commercial Warranty
- Warranty conditions on [www.berryalloc.com](http://www.berryalloc.com)

